

Listing of the Claims:

1 1. (Currently amended) A cabinet for enclosing a controller, said controller being
2 subject to arcing, which produces arc gasses, said cabinet comprising:

3 a plurality of walls for enclosing said controller;

4 a roof panel connected to said plurality of walls;

5 an exhaust vent for discharging built up gasses generated during an arc fault
6 event;

7 a floor panel connected to said plurality of walls; and

8 a door for accessing said controller and maintaining integrity of said cabinet
9 during said arc fault event.

10 a first member disposed parallel to one of said plurality of walls;

11 a second member connecting said first member to said one of said plurality of
12 walls;

13 a hinge connecting said door to one of said first member, said second member,
14 and said one of said plurality of walls;

15 a channel attached to said door and extending over said hinge, said channel
16 adapted for receiving an edge of said first member, said edge opposite said second
17 member; and

18 a resilient seal disposed between said edge and said channel as said channel is
19 forced toward said edge of said first member due to arc gasses produced during arcing.

Claims 2-7 (Canceled)

1 8. (Previously presented) The cabinet of claim 1 further comprising a latching
2 mechanism for releasably securing said door in a closed position, said latch mechanism

3 including a plurality of latch hooks and a strike assembly receiving said plurality of latch
4 hooks such that said door remains sealed during said arcing.

1 9. (Original) The cabinet of claim 1 further comprising:

2 an opening bounded by a wall edge of one of said plurality of walls;

3 an access panel having a first surface and a first panel edge with a protruding
4 member extending toward said wall edge; and

5 a resilient seal disposed between said first surface of said access panel and said
6 wall edge.

1 10. (Currently amended) The cabinet of claim 1 further comprising:

2 an opening bounded by a first edge of one of said plurality of walls and by a
3 second edge of another one of said plurality of walls;

4 an access panel having a first surface and a second surface, a first panel edge with
5 a first protruding member extending toward said first edge, and a second panel edge with
6 a second protruding member extending toward said second edge,

7 a first resilient seal disposed between said first surface of said access panel and
8 said first edge; and

9 a second resilient seal disposed between said second surface of said access panel
10 and said second edge.

1 11. (Currently amended) A cabinet for enclosing a controller, said controller being
2 subject to arcing, which produces arc gasses, said cabinet comprising:

3 a plurality of walls for enclosing said controller;

4 a roof panel connected to said plurality of walls;

5 a floor panel connected to said plurality of walls;
6 an exhaust vent for discharging said arc gasses;
7 a flap covering said exhaust vent, said flap adapted to open and allow said arc
8 gasses to escape;
9 a hinge connecting said flap to said cabinet;
10 a door for accessing said controller;
11 a latching mechanism for releasably securing said door in a closed position, said
12 latch mechanism including a plurality of latch hooks and a strike assembly receiving said
13 plurality of latch hooks such that said door remains sealed during said arcing;
14 a first member disposed parallel to one of said plurality of walls;
15 a second member connecting said first member to said one of said plurality of
16 walls;
17 a hinge connecting said door to one of said first member, said second member,
18 and said one of said plurality of walls;
19 a channel attached to said door and extending over said hinge, said channel
20 adapted for receiving an edge of said first member; and
21 a resilient door seal disposed between said edge and said channel as said channel
22 is forced toward said edge of said first member due to arc gasses produced during arcing.

1 12. (Currently amended) The cabinet of claim 11 further comprising:
2 an opening bounded by a first inwardly turned edge of one of said plurality of
3 walls and by a second inwardly turned edge of another one of said plurality of walls;
4 an access panel having a first surface and a second surface, a first outwardly
5 turned panel edge with a first protruding member extending toward said first inwardly

6 turned edge, and a second outwardly turned panel edge with a second protruding member
7 extending toward said second inwardly turned edge,

8 a first resilient seal disposed between said first surface of said access panel and
9 said first inwardly turned edge; and

10 a second resilient seal disposed between said second surface of said access panel
11 and said second inwardly turned edge.

1 13. (Original) The cabinet of claim 11 further comprising:

2 a first dimple in a first surface selected from one of said roof panel, said floor
3 panel, one of said plurality of walls, and a structural member; and

4 a second dimple in a second surface selected from one of said roof panel, said
5 floor panel, one of said plurality of walls, and said structural member, said second dimple
6 adapted to mate with said first dimple.

1 14. (Original) The cabinet of claim 13 further comprising:

2 a first opening in said first surface being center aligned within said first dimple;

3 a second opening in said second surface being center aligned within said second
4 dimple and in register with said first opening when said first dimple is mated with said
5 second dimple; and

6 a fastener disposed in said first opening and said second opening, said fastener
7 securely mating said first and second dimples such that said mated dimples provide an
8 increased shear strength to said fastener.

1 15. (Original) The cabinet of claim 11 further comprising a baffle for isolating a first
2 volume of said cabinet from a second volume of said cabinet, said baffle connected to at
3 least two of said plurality of walls.

16. (Canceled)

1 17. (Currently amended) A cabinet for enclosing a controller, said controller being
2 subject to arcing, which produces arc gasses, said cabinet comprising:

3 a plurality of walls for enclosing said controller;

4 a door for accessing said controller, said door including a latching mechanism for
5 releasably securing said door in a closed position, said latch mechanism including a
6 plurality of latch hooks and a strike assembly receiving said plurality of latch hooks such
7 that said door remains sealed during said arcing;

8 a first member disposed parallel to one of said plurality of walls;

9 a second member connecting said first member to said one of said plurality of
10 walls;

11 a hinge connecting said door to one of said first member, said second member,
12 and said one of said plurality of walls;

13 a channel attached to said door and extending over said hinge, said channel
14 adapted for receiving an edge of said first member; and

15 a resilient door seal disposed in said channel for sealing a gap between said edge
16 and said channel as said channel is forced toward said edge of said first member due to
17 arc gasses produced during arcing.

Claims 18 and 19 (Canceled)

1 20. (Currently amended) ~~A cabinet for enclosing a controller, said controller being~~
2 ~~subject to arcing, which produces arc gasses, said cabinet comprising:~~ The cabinet of
3 claim 17, further comprising:

4 ~~a plurality of walls for enclosing said controller;~~

5 a baffle for isolating a first volume of said cabinet from a second volume of said
6 cabinet, said baffle connected to at least two of said plurality of walls, said first volume
7 containing said arc gasses;

8 [[a]] at least one dimple in at least two of said plurality of walls; and

9 [[a]] at least two dimples in said baffle, said baffle dimples adapted to mate with
10 said wall dimples thereby providing a high [[sheer]] shear strength attachment between
11 said plurality of walls and said baffle.

Claims 21-27 (Canceled)

1 28. (Previously presented) The cabinet of claim 20 further comprising

2 an aperture centrally defined in each of said wall dimples and in each of said
3 baffle dimples such that said apertures in said wall dimples are in register with said
4 apertures in said baffle dimples when said wall dimples are mated with said baffle
5 dimples; and

6 a fastener disposed in said registered apertures of said wall dimples and said
7 baffle dimples, said mated dimples providing increased shear strength to said fastener
8 securing said walls to said baffle.

29. (Canceled)

1 30. (Currently amended) The cabinet of claim [[29]] 17 further comprising:

2 an opening bounded by a first inwardly turned edge of one of said plurality of
3 walls and by a second inwardly turned edge of another one of said plurality of walls;

4 an access panel having a first surface and a second surface, a first outwardly
5 turned panel edge with a first protruding member extending toward said first inwardly
6 turned edge, and a second outwardly turned panel edge with a second protruding member
7 extending toward said second inwardly turned edge,

8 a first resilient seal disposed between said first surface of said access panel and
9 said first inwardly turned edge; and

10 a second resilient seal disposed between said second surface of said access panel
11 and said second inwardly turned edge.

1 31. (Currently amended) An arc resistant cabinet for enclosing electrical equipment
2 subject to arcing faults that produce arc gasses, said cabinet comprising:

3 a plurality of walls for enclosing said electrical equipment;

4 a roof panel connected to said plurality of walls;

5 a floor panel connected to said plurality of walls;

6 an opening bounded by a first inwardly turned edge of one of said plurality of
7 walls and by a second inwardly turned edge of another one of said plurality of walls;

8 an access panel having a first surface and a second surface, a first outwardly
9 turned panel edge with a first protruding member extending toward said first inwardly
10 turned edge, and a second outwardly turned panel edge with a second protruding member
11 extending toward said second inwardly turned edge,

12 a first resilient seal disposed between said first surface of said access panel and
13 said first inwardly turned edge; and

14 a second resilient seal disposed between said second surface of said access panel
15 and said second inwardly turned edge.

1 32. (Currently amended) ~~An arc resistant cabinet for enclosing electrical equipment~~
2 ~~subject to arcing faults that produce arc gasses, said cabinet comprising:~~ The cabinet of
3 claim 17, further comprising:

4 a plurality of structural members

5 ~~a plurality of walls for enclosing said electrical equipment;~~

6 a roof panel connected to said plurality of walls;


7 a floor panel connected to said plurality of walls;

8 a plurality of dimples, at least one dimple being defined in each of said plurality
9 of structural members, said plurality of walls, said roof panel and said floor panel, each of
10 said plurality of dimples defining a central aperture and being configured for mating with
11 another of said plurality of dimples such that said central apertures of mated dimples are
12 generally aligned; and

13 a plurality of fastening devices, one being received in said generally aligned
14 central apertures of mated dimples, said mated dimples providing increased [[sheer]]
15 shear strength between said plurality of structural members, said plurality of walls, said
16 roof panel and said floor panel of said cabinet.

PATENT
USSN: 10/058,863

Respectfully submitted,

A handwritten signature in cursive script, appearing to read "Larry T. Shrout", written in dark ink.

Larry T. Shrout
Registration No. 35,357

SQUARE D COMPANY
P.O. Box 27446
Raleigh, North Carolina 27611-7446
Telephone: 919/266-8625
Facsimile: 919/266-8397